Index No. R5

CASS COUNTY LAND CORNER RECORD

T. 140 R. 30 M. 5TH Coordinates: X _____ Y _____

NE 30 Corner common to sections 19,20,29,30



EXISTING SURVEYS

Original Government Survey

Year surveyed 1865

Original monument POST

Bearing Trees

Species	TAM	TAM.	TAM.	
Diameter	4"	5"	5"	
Bearing	S5E	S47W	N60W	
Distance	125 LKS	42 LKS	255 LKS	

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1910 By JOHN CURO

Location filed COUNTY SURVEY RECORD BOOK B" P. 75-80

Monument FND CORNER SET BY CURO, OLD GOVT B.T: 5" TAM S47W 2.72' ALSO CURO'S B.TS: 7" TAM STUMP NE 1.70', 3" TAM STUMP NW 8.25' SET 3x3x60" STAKE, 1915 B.TS IN PLACE & STAKE ALSO ON MICRO F.H. - ROLL 105, BK 48, P. 28

Bearing Trees, Reference Objects

Species				
Diameter				
Bearing				
Distance				

Evidence of Subsequent Corner Restoration

Year of search — By —

BOOK "C" P437 IRON MONUMENT

Bearing Trees, Reference Objects

R-5

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed

Monument

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

PLAT - POQUET SHORES
R.F. SCHNEIDER 1966

PLAT - SIEVERS ACRES ADDITION TO HALKENSACK
ROGER MUSTONEN 1978

Certificate - Jim Nielsen - Mnn DOT - 1983
Doc. # 267931
Set MN/DOT cast iron monument bolted to top of 2"x2"x8' metal post up 2'. Ties: 1" pinched pipe S 57° 45' W 50.94'; Channel post 1' North; 10" Triple Birch S 3° 52' E 649.67'; 10" Jack Pine S 1° 03' W 644.61'; 10" Jack Pine S 9° 15' W 579.33'.

9-16-04 J. Leas # 42619
Cert of Survey Shows monument found

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____