

Index No. \_\_\_\_\_

CASS COUNTY LAND CORNER RECORD

T. \_\_\_\_\_ R. \_\_\_\_\_ M. \_\_\_\_\_ Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_

Corner common to sections \_\_\_\_\_



= Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed \_\_\_\_\_  
Original monument \_\_\_\_\_

Original Evidence Found

Year of search \_\_\_\_\_ by \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Original Bearing Trees Found

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed:  
Monument:

Evidence of Subsequent Corner Restoration

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Location filed:  
Monument:

Bearing Trees, Reference Objects

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Bearing Trees, Reference Objects

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_


Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed:  
Monument:

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Location filed:  
Monument:

T. 140 R. 30 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 34 Corner common to sections 26, 27, 34, 35



EXISTING SURVEYS

Original Government Survey

Year surveyed 1865  
Original monument POST

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Species	Bearing Trees			
	W. PINE	W. PINE	N. PINE	N. PINE
Diameter	<u>24"</u>	<u>24"</u>	<u>12"</u>	<u>10"</u>
Bearing	<u>N77E</u>	<u>N37W</u>	<u>S76W</u>	<u>S8E</u>
Distance	<u>138 LKS</u>	<u>71 LKS</u>	<u>80 LKS</u>	<u>190 LKS</u>

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1948 By HAROLD CURD  
Location filed COUNTY BOOK "D" P. 334  
Monument FIND 2" PINE  
1954, HAROLD CURD, BOOK "D" P. 375 FIND 2" I.P. AND  
TIES BELOW TIE TO SW IS 6" W. OAK

Evidence of Subsequent Corner Restoration

Year of search 1914 By Harry Todd  
microfilm - roll 115 BK 73 - P. 77  
Find stamps of NE, NW & SE trees set  
corner P. 81 - set 2448" I.P.  
1914 - Gorman - microfilm - roll 115 BK 92 P. 28  
Find corner.

Bearing Trees, Reference Objects

Species	W. OAK	BASSWOOD	?	W. OAK
Diameter	<u>10"</u>	<u>8"</u>	<u>?</u>	<u>20"</u>
Bearing	<u>N30-45E</u>	<u>S63-23E</u>	<u>S20-20W</u>	<u>N78-25W</u>
Distance	<u>70.65'</u>	<u>35.7'</u>	<u>42.35'</u>	<u>92.60'</u>

1948 TIES

Bearing Trees, Reference Objects

Species	OAK	OAK	OAK	Poplar
Diameter	<u>12"</u>	<u>4"</u>	<u>2"</u>	<u>6"</u>
Bearing	<u>N78-05W</u>	<u>S77-47W</u>	<u>S40-37E</u>	<u>N61-13E</u>
Distance	<u>93.00</u>	<u>77.50</u>	<u>51.20'</u>	<u>50.95'</u>

1914 - Todd

V-17

Subsequent Corner Restoration

Year surveyed 6/2000 By CCSO  
Location filed file # 98031  
Monument Found R/R spike down 0.5'  
4' E. of & 32nd St. 15' E N. of  
fence line to west. Witnesses are:

<u>3" Elm</u>	<u>N52°W</u>	<u>37.14'*</u>
<u>4" Ash</u>	<u>N50°E</u>	<u>40.70'*</u>
<u>8" W. Oak</u>	<u>S88°E</u>	<u>27.01'*</u>
<u>Fence Cor</u>	<u>S63°W</u>	<u>29.59'*</u>

\* distance to double head nail

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_