Index No. J1

CASS COUNTY LAND CORNER RECORD

T. 140 R. 31 M. 5TH Coordinates: X _____ Y _____
NW 18 Corner common to sections 7, 18



EXISTING SURVEYS

Original Government Survey

Year surveyed 1860
Original monument POST

Bearing Trees

Species	OAK	PINE	PINE	PINE
Diameter	6"	24"	36"	12"
Bearing	S3RE	N28W	S85W	N55E
Distance	36 LKS	33 LKS	64 LKS	59 LKS

Original Evidence Found

Year of search 5/83 By #7203
Monument found 1/2" IRON PIPE
DON BUSKER HUBBARD CTY

~~Original~~ Bearing Trees ~~Found~~

Species	12" ASPEN	6" W. PINE	10" R. OAK	
Diameter	WNW TO	NE TO	SW TO	
Bearing	AH NAIL	AH NAIL	AH NAIL	
Distance	34.14	44.42	36.38	

SET HUBBARD CAST IRON - HUBBARD CERTIFIED

Subsequent Corner Restoration

Year surveyed 1967 By R.F. SCHNEIDER
Location filed
Monument FND 2" GALV. I.P. W/CAP IN G RD.
POSSIBLE NEF SW B.T. STUMPS.
1982 FREEMAN, OLSON - FND R.R. SPIKE SET OVER 2" I.P. AND NW, SW, SE TIES (BELOW)

Bearing Trees, Reference Objects

Species	J. PINE	R. OAK	POPLAR	POPLAR SNAG
Diameter	6"	9"	7"	12"
Bearing	S56E	S43W	N70W	S86E
Distance	54.15'	36.12'	34.1'	36.4'
	OLD			OLD

1967 TIES

Evidence of Subsequent Corner Restoration

Year of search 2002 By R. Mustorn #11946
Cert. of Suv. shows Mon. found

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed
Monument Corner GPS CCSO 9/11/02
CCSO Fd. CIM, down 1.0'; 2' ± W. of E

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____
Filed at _____ Date _____