


Index No. T 25

CASS COUNTY LAND CORNER RECORD

T. 140 R. 31 M. 5th Coordinates: X _____ Y _____
E14 25 Corner common to sections 25 AND 30-140-30



EXISTING SURVEYS

Original Government Survey

Year surveyed 1865
Original monument Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees

Species Y. PINE Y. PINE
Diameter 12" 12"
Bearing N 64 3/4 E S 84 W
Distance 23 LKS 23 LKS

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed 1983 By MN/DOT
Location filed Corner Certificate Doc # 267918
Monument Set Cast iron (doubled dist from NE to NW on E Line)

Evidence of Subsequent Corner Restoration

Year of search 1983 (March) By Freeman - Olson
Survey Tech - Forester
Find Minn DOT Cast iron and all ties
Tag on Tie tree - Twin 12 & 14" R. oak S 85 W 17.32'

Bearing Trees, Reference Objects

Species W. oak Tw. R. oak R. oak
Diameter 6" 16" 12"
Bearing N 35 W N 85 W S 17 W
Distance 3.55' 17.31' 32.86'

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Certificate - Jim Nielsen - Minn DOT - 1983
(info on other side)
July 1905, Twp rd order shows no survey
June 1908 Twp rd order shows no survey

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____