


T. 140 R. 31 M. 5TH Coordinates: X _____ Y _____
N1/4 34 Corner common to sections 27, 34



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1870
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees
Species S.P. PINE S.P. PINE
Diameter 14" 16"
Bearing N15W S37W
Distance 17 LKS. 14 LKS.

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed 1920 By E.B. Horst
Location filed Curo Notes Bk. 166, pg 22
Monument Set 2 1/2" x 30" i.m. from old U.S.B.T.s

Evidence of Subsequent Corner Restoration

Year of search Sept 2003 By CCSO
Set alum cap telespar, up 1.0', in found corner post hole, 38' ± E. of Goose Lake trail.

Bearing Trees, Reference Objects

Species N. Pine
Diameter 14"
Bearing N38°45'E
Distance 209.9'

Bearing Trees, Reference Objects

N. Pine N. Pine W. Pine
18" 14" 15"
N22°W S70°W S31°W
57.24' 24.92' 49.26'
dbl hd nail dbl hd nail dbl hd nail

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument May 2004 T. Freeman # 21367
Cert. of Sur. Shows mon. found

Evidence of Subsequent Corner Restoration Found

Year of search July 2005 By T. Freeman #21367
Cert. of Survey shows monument found

July 1905, Top rd order shows no survey