


T. 141 R. 27 M. 5th Coordinates: X _____ Y _____
N 1/4 10 Corner common to sections 3, 10



EXISTING SURVEYS

Original Government Survey

Year surveyed 1874
Original monument Post

Original Evidence Found

Year of search _____ by _____
Monument found _____

Bearing Trees

Species	<u>Oak</u>	<u>Oak</u>
Diameter	<u>4"</u>	<u>4"</u>
Bearing	<u>N 15° E</u>	<u>S 52° E</u>
Distance	<u>10 links</u>	<u>13 links</u>

Original Bearing Trees Found

Species	_____	_____
Diameter	_____	_____
Bearing	_____	_____
Distance	_____	_____

Subsequent Corner Restoration

Year surveyed 1919 By E.G.Harrington, GLO
Location filed: Resurvey Notes, Minnesota Historical Society
Monument:
Ran line, no mention of this corner.

Evidence of Subsequent Corner Restoration

Year of search 3/1972 By W.J. Spain, LS 2003
Location filed: Plat La Casa J & R, Doc. #204321
Monument: Shown
Corner shown on S. line of plat.

Bearing Trees, Reference Objects

Species	_____	_____
Diameter	_____	_____
Bearing	_____	_____
Distance	_____	_____

Bearing Trees, Reference Objects

Species	_____	_____
Diameter	_____	_____
Bearing	_____	_____
Distance	_____	_____

Subsequent Corner Restoration

Year surveyed 6/1981 By R.A. Mustonen, LS 11395?
Location filed: Certificate of Survey, #521
Monument: Indicates Iron Monument set

10/1987, R.L. Kovanen, LS 16459
Certificate of Location
Found 2.5" iron pipe as indicated on S. line of plat.

Evidence of Subsequent Corner Restoration Found

Year of search 7/2018 By CCHD/SO
Location filed: #2017.018
Monument: Found USFS 2" iron pipe with brass cap in tree line of Spruce and witnessed.
14" White Oak, N 80° E, 24.20'(1988) 20d spike, up 0.5', N.
10" Red Pine, N 72° W, 19.95' duplex nail, up 1.0', S. side
14" Red Oak, N 9° W, 99.45' duplex nail, up 1.0', W. side


1/1988, R.L. Kovanen, LS 16459
Certificate of Location
Replace 2.5" pipe with USFS 2" iron pipe with brass cap, in lawn and witness as follows.
5" Birch, S 88° W, 23.43' 20d spike
11" White Oak, N 80° E, 24.20' 20d spike
8" Red Oak, S 11° W, 35.10' 20d spike

7/2007, B.W. Skipton, LS 17768
Certificate of Survey for Hillstrom, #3648
Indicates Cast Iron Monument found.

Index No. E 15

CASS COUNTY LAND CORNER RECORD

T. 141 R. 27 M. 5TH Coordinates: X _____ Y _____
N 1/4 10 Corner common to sections 3, 10



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1874
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees

Species	<u>OAK</u>	<u>OAK</u>	_____
Diameter	<u>4"</u>	<u>4"</u>	_____
Bearing	<u>N 1/2 E</u>	<u>S 5/2 E</u>	_____
Distance	<u>10 LKS</u>	<u>13 LKS</u>	_____

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration

Year of search 1988 By Robert Kovanen
Corner Certificate - Doc # 302623

Set 2x36" lip. w/ brass cap in place of found 2 1/2" iron

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Bearing Trees, Reference Objects

<u>W. oak</u>	<u>Red Oak</u>	<u>Birch</u>
<u>11"</u>	<u>8"</u>	<u>5"</u>
<u>N 80 E</u>	<u>S 11 W</u>	<u>S 88 W</u>
<u>24.20'</u>	<u>35.10'</u>	<u>23.43'</u>

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
PLAT - LA CASA JIR
W.J. SPAIN JR 1972

Certificate - Robert Kovanen - 1988

Remonumentation certificate prepared _____ By _____
Filed at _____ Date _____