


Index No. L-M 9

CASS COUNTY LAND CORNER RECORD

T. 141 R. 27 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
WC, CC Corner common to sections 17, 16  
N0°30'E 4.25 CH.



EXISTING SURVEYS

Original Government Survey

Year surveyed 1919  
Original monument N36°1'P W/BRASS CAP WC 1919  
T141N/R27W S17/S16

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees WC 1919  
Species R. OAK ELM  
Diameter 16" 20"  
Bearing N9E N8-15W  
Distance 138 LKS. 118 LKS.

Original Bearing Trees Found

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

○ = Corner

Subsequent Corner Restoration

Year surveyed 1982 By Gary Stevenson  
Location filed Corner Certificate  
Monument in 1980 USFS find brass cap and both  
1919 B.T.'S below.

Evidence of Subsequent Corner Restoration

Year of search \_\_\_\_\_ By \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Bearing Trees, Reference Objects

Species W. oak Ash Elm W. oak  
Diameter 9" 7" 23" 19"  
Bearing N51W N37W N8W N9E  
Distance 116.8' 97.0' 77.9' 91.1'  
1919 B.T.'S

Bearing Trees, Reference Objects

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Certificate - Gary Stevenson - filed by USFS 1984  
Doc. # 279272 dated 1982

1999 - Landecker + Assoc.  
Cert. of Survey indicates brass  
capped monument found.

Remonumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
Filed at \_\_\_\_\_ Date \_\_\_\_\_