Index No. U-V 17

CASS COUNTY LAND CORNER RECORD

T. 141 R. 27 M. 5TH Coordinates: X _____ Y _____

MC # 16 Corner common to sections 26,27



EXISTING SURVEYS

Original Government Survey

Year surveyed 1874

Original monument POST

Bearing Trees

Species	FIR	BRIAR		
Diameter	6"	6"		
Bearing	N13W	S64E		
Distance	11 LKS	19 LKS.		

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1974-1978 By MILO STEFAN

Location filed PLAT OF SURVEY "E-72"

Monument 2"X 5' GALV. I.P. W/ 3" BRASS CAP. CORNER RESTORED IN 1968. AFFIDAVIT FILED IN CASS COUNTY RECORDS ON PAGE 636. 1979 LINCOLN MACKEY, BOOK "C" P.378, CHAIN N. FROM CORNER

Bearing Trees, Reference Objects

Species				
Diameter				
Bearing				
Distance				

Evidence of Subsequent Corner Restoration

Year of search _____ By _____

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

CERTIFICATE - BILL OKERMAN - 1968
Found car axle marking corner; 6" Fir N13W 7.3' now stump. Set 6"x5' cylindrical concrete monument capped with 3" bronze stamped tablet. Ties: 10" Elm N71E 67.48'; 14" Elm N28E 145.65'; 10" Basswood N43W 104.54'.
1994 3.14: Placed 2"x48" iron pipe w/brass cap up 14'. 5-4-94 Cert. Filed by Terry Freeman, RLS 21367, Doc # 357313. Ties: 3" Balsam N30E 16.08; 4" Balsam N50W 33.54; 5" Birch S84E 16.21'

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____