


Index No. 215

CASS COUNTY LAND CORNER RECORD

T. 141 R. R7 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
514 34 Corner common to sections 34



EXISTING SURVEYS

**Original Government Survey**

Year surveyed 1865  
Original monument POST

**Bearing Trees**

Species	<u>W. PINE</u>	<u>BL. OAK</u>	_____	_____
Diameter	<u>20"</u>	<u>6"</u>	_____	_____
Bearing	<u>N39W</u>	<u>N52E</u>	_____	_____
Distance	<u>77 LKS</u>	<u>25 LKS</u>	_____	_____

**Original Evidence Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

**Original Bearing Trees Found**

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

**Subsequent Corner Restoration**

Year surveyed 1913 By HARRY S. TODD  
Location filed COUNTY SURVEY RECORD BOOK "A" P568-570  
Monument SET 4x4x90" STAKE

**Evidence of Subsequent Corner Restoration**

Year of search 1974-1978 By MILD STEFAN  
PLAT OF SURVEY "E-TR" 2'x5' GALV. I.P. W/3'  
BRASS CAP PROPORTIONED.

**Bearing Trees, Reference Objects**

Species	<u>W. PINE STUMP</u>	_____	_____	_____
Diameter	<u>26"</u>	_____	_____	_____
Bearing	<u>N51-15E</u>	_____	_____	_____
Distance	<u>12.63'</u>	_____	_____	_____

**Bearing Trees, Reference Objects**

<u>R. PINE</u>	<u>R. PINE</u>	<u>R. OAK</u>	<u>STEEL SIGN POSTS</u>	_____
<u>19"</u>	<u>24"</u>	<u>12"</u>	_____	_____
<u>N13E</u>	<u>N48E</u>	<u>N52W</u>	<u>EAST</u>	<u>WEST</u>
<u>188.5'</u>	<u>131.4'</u>	<u>96.5'</u>	<u>3.7'</u>	<u>5.8'</u>

**Subsequent Corner Restoration**

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

**Evidence of Subsequent Corner Restoration Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_

Re monumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
Filed at \_\_\_\_\_ Date \_\_\_\_\_