Index No. 25

CASS COUNTY LAND CORNER RECORD

T. 141 R. 27 M. 5TH Coordinates: X _____ Y _____

SE 31 Corner common to sections 31, 32



EXISTING SURVEYS

Original Government Survey

Year surveyed 1865

Original monument Lost

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species	W. Pine	Fir		
Diameter	10"	6"		
Bearing	N10W	N26E		
Distance	96 LKS	104 LKS		

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1912 By Harry S Todd

Location filed County Survey Record Book "A" P 520-522

Monument Fnd old Govt B.T: 10" W. Pine N10W 96 LKS

also on microfilm - roll IDS BK69 P.72

Evidence of Subsequent Corner Restoration

Year of search 1919 By GLO

Filed at: Secretary of State. Fnd 2" Galv. I.P established by Co. Surveyor from N.W B.T. Set 2x36" I.P w/brass cap - set 36" in ground - falls in road

S.C

T141N	R27W
531	532
1919	

Bearing Trees, Reference Objects

Species	Poplar			
Diameter	4"			
Bearing	N32-33E			
Distance	112.30'			

Bearing Trees, Reference Objects

Poplar	Ash			
4"	8"			
N43W	N79E			
100 LKS	351 LKS			

Subsequent Corner Restoration

Year surveyed Mar 2003 By CCSO

Location filed

Monument Found 60d spike, down 0.1', 49' ± S. of ℄ Co Rd #7, on E of road to North.

* 11" W. Oak N28°W 129.28'

* 6" Spruce S20°E 53.04'

*20" R. Pine S55°W 29.28'

* - Dist meas. to dbl bd nail

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____