


Index No. A 9

CASS COUNTY LAND CORNER RECORD

T. 141 R. 28 M. 5TH Coordinates: X NE 5 Y 4, 5 AND 32, 33-142-28
Corner common to sections



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing	Trees
<u>Y. PINE</u>	<u>POPLAR</u>	
<u>12"</u>	<u>4"</u>	
<u>S35E</u>	<u>N45W</u>	
<u>100 LKS</u>	<u>80 LKS</u>	

Original Bearing Trees Found

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration

Year surveyed 1916 By JOHN CURD, E.B. HORST
Location filed COUNTY BOOK "B" P391-398
Monument FIND OLD POST AND STUMP HOLE DE OLD GUM
BIT: 12" N. PINE S35E 100 LKS. SET NEW POST
SET IRON MONUMENT

Evidence of Subsequent Corner Restoration

Year of search 1921 By GLO
FILED AT: SECRETARY OF STATE FIND 2" GALV. I.P.
AND GUM BIT: 16" DEAD PINE S35E 107 LKS
SET 2x 30" I.P.W/BRASS CAP 7142 N R28W
532 | 533
55 | 54

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>J. PINE</u>	<u>14"</u>	<u>S24-10W</u>	<u>74.60'</u>
<u>N. PINE</u>	<u>14"</u>	<u>S35-50E</u>	<u>69.60'</u>

TIES IN PLACE

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>R. OAK</u>	<u>10"</u>	<u>S66 1/2 E</u>	<u>64 LKS</u>
<u>N. PINE</u>	<u>14"</u>	<u>S28 3/4 W</u>	<u>102 LKS</u>
<u>R. OAK</u>	<u>6"</u>	<u>N66 1/4 W</u>	<u>170 LKS</u>

7141 N 1921

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
CERTIFICATE - BILL OKERMAN - 1971
Set 5 1/2 x 5 1/2 x 24" concrete monument
with brass cap. Ties: 5" W. OAK N64 W
141.60'; 5" W. OAK N54E 70.90'; 12" N.
PINE S15E 76.30'; 7" W. OAK S40W 134.60

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____