


Index No. C15

CASS COUNTY LAND CORNER RECORD

T. 141 R. 28 M. 5th Coordinates: X _____ Y _____
C1/4 Corner common to sections 3



○ = Corner

EXISTING SURVEYS

Original Government Survey
Year surveyed 1921
Original monument 1x36" I.P.W. BRASS C1/4 53
CAP 1921

Original Evidence Found
Year of search 1997 By MN DOT
Monument found GLO Brass
Cap.

Bearing Trees
Species ELM W. OAK
Diameter 8" 8"
Bearing 50-30E N1W
Distance 102 LKS 63 LKS

Original Bearing Trees Found
Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration
Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration
Year of search 1999 By ES&S James Kramer
Fd. GLO Monument up 1.0'
Certificate filed as #410193

Bearing Trees, Reference Objects
Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects
Burr Oak Ash Ash Maple
12" 15" 6" 15"
N 2° E S 60° E S 10° E S 80° W
7.38'* 23.51'* 17.12'* 25.20'*
** distance to copper nail and disk.*

C-15

Subsequent Corner Restoration
Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found
Year of search 1999 By MN DOT
Cert. of Survey indicates a
GLO monument fnd.

Remonumentation certificate prepared _____ By _____
Filed at _____ Date _____