Index No. C 17

CASS COUNTY LAND CORNER RECORD

T. 141 R. 28 M. 5TH Coordinates: X _____ Y _____

E 1/4 3 Corner common to sections 2,3



EXISTING SURVEYS

Original Government Survey

Year surveyed 1874

Original monument POST

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species	OAK			
Diameter	10"			
Bearing	S80W			
Distance	150 LKS			

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1918 By GLO

Location filed SECRETARY OF STATE

Monument FND OLD GOV'T B.T.: 16" ELM S80W 150LKS.
SET 1X36" I.P. W/ BRASS CAP 1/4
S3 | S2
1918

Evidence of Subsequent Corner Restoration

Year of search 1987 By Walt Curo

Certificate - Doc # 301672

Found GLO monument

Bearing Trees, Reference Objects

Species	W. OAK	BL. OAK		
Diameter	12"	6"		
Bearing	N59 1/2 E	S33W		
Distance	124 LKS	32 LKS		

Bearing Trees, Reference Objects

Burr oak	Red oak	Red oak	Burr oak
12"	10"	24"	15"
N3W	S31E	S35W	S63W
34.30'	7.20'	68.70'	56.56'

C-17

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

PLAT - TOWNLINE SHORES
R.F. SCHNEIDER 1972

Certificate - Walt Curo - 1987

1999 - ~~[illegible]~~ MN/DOT Cert. of Loc. Doc. # 410189
Fd. - 6" SPK., set flush at edge of gravel rd.

TIES: 12" Burr Oak N 3° W 34.30'
6" Twin R. Oak copper nail + disc (no dist. given)
24" R. Oak stump S 35° W 68.70'
15" Burr Oak S 63° W 56.56'

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____