


Index No. D17

CASS COUNTY LAND CORNER RECORD

T. 141 R. 28 M. 5TH Coordinates: X _____ Y _____
S116 Corner common to sections 2,3



○ = Corner

EXISTING SURVEYS

Original Government Survey
Year surveyed 1918 S116
Original monument 1x36" 1P.W./BRASS 53/52
CAP 1918

Original Evidence Found
Year of search 1997 By MN/DOT
Monument found GLO Brass
Cap

Bearing Trees
Species W.OAK W. OAK _____
Diameter 10" 5" _____
Bearing S86E N6 1/2 W _____
Distance 154 LKS 65 LKS _____

Original Bearing Trees Found
Species W. Oak (STP) _____
Diameter 24" _____
Bearing N6°W _____
Distance 43.10 _____

Subsequent Corner Restoration
Year surveyed 1997 By James Kramer
Location filed MN/DOT Baxter office
Monument GLO Brass Cap, Certificate
filed #410188

Evidence of Subsequent Corner Restoration
Year of search _____ By _____

Bearing Trees, Reference Objects
Species Pin Maple Twin Bur Oak Fence Cor Steel Post
Diameter 10" 10" _____
Bearing N80°W S85°W SW West
Distance 53.40* 64.60* 5.80* 4.0'
* distance to copper nail and disk.

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Evidence of Subsequent Corner Restoration Found

Year surveyed _____ By _____
Location filed _____
Monument _____

Year of search _____ By _____

