


T. 141 R. 28 M. 5th Coordinates: X _____ Y _____
NE 9 Corner common to sections 3, 4, 9, 10



EXISTING SURVEYS

Original Government Survey

Year surveyed 1874
 Original monument POST

Original Evidence Found

Year of search 1919 By GLD
 Monument found 2" GALV. I.P.

Species	Bearing	Tree	Distance
<u>POPLAR</u>	<u>W. PINE</u>	<u>W. PINE</u>	
<u>8"</u>	<u>26"</u>	<u>13"</u>	
<u>S26W</u>	<u>S65E</u>	<u>N43E</u>	
<u>40 LKS</u>	<u>59 LKS</u>	<u>35 LKS</u>	

Species	Bearing	Tree	Distance
<u>W. PINE</u>	<u>DECIDUOUS</u>		
<u>40"</u>	<u>STUMP</u>		
<u>S51E</u>	<u>N46 1/2 E</u>		
<u>59 LKS</u>	<u>35 LKS</u>		

O = Corner

Subsequent Corner Restoration

Year surveyed 1915 By JOHN CURO
 Location filed COUNTY SURVEY RECORD BOOK "B" P. 169-177
 Monument FIND OLD GOVT B.T.S: STUB 26" W. PINE S62E
59 LKS, ROOTS: 13" W. PINE N43E 35 LKS. SET 400
SET 2 1/2 X 4 1/2" CAPPED IRON
also on microfilm - roll NO 5 BK 60 P. 108-109

Evidence of Subsequent Corner Restoration

Year of search 1919 By GLD
 FILED AT: SECRETARY OF STATE. FIND 2" I.P.
 AND GOVT B.T.S (ABOVE) SET 2X36" I.P. w/ BRASS
 CAP. T.I.YIN R28W
54 | 53
59 | 510
1918

Bearing Trees, Reference Objects

Species	Bearing	Distance
<u>oak</u>		
<u>12"</u>		
<u>S65W</u>		
<u>39.85'</u>		

Bearing Trees, Reference Objects

Species	Bearing	Distance
<u>POPLAR</u>	<u>W. OAK</u>	<u>POPLAR</u>
<u>6"</u>	<u>18"</u>	<u>14"</u>
<u>N45E</u>	<u>S66 1/2 W</u>	<u>N73W</u>
<u>113 LKS.</u>	<u>61 LKS.</u>	<u>109 LKS</u>

E-13

Subsequent Corner Restoration

Year surveyed 8/2001 By CCSO
 Location filed CCSO
 Monument Found Brass cap per 1999
MN/DOT cert. and witnesses.
Add witness NE as "X" is head
to see on rock.

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
 CERTIFICATE - WALT CURO - 1982
 DOC. # 263109
 Found 6" SPIKE 1 1/2' below surface. TIES:
7" TAMARACK N74W 119.53'; "X" on 3' dia.
ROCK N40E 87.47'; 4" WHITE OAK S44E
120.26'; "X" on concrete abutment over
center of CULVERT S45W 75.52'.

USFS Rd Post N28°E, 58.59*
*distance to double head nail

MN/DOT
1999 - ~~650~~ Cert. of Loc. Doc. # 410187
Fd. - 2" I.P. w/ Brass Cap Down. 0.10' at inter-
section of T.H. 200 and N-S TWP Rd.
Ties are the same as noted above,
with exception to the size of the trees:

- 7" Tam. is now 15"
- 4" W. OAK is now 6"

- Cert. of Survey indicates 2" I.P. w/
brass cap find.