

Index No. _____

CASS COUNTY LAND CORNER RECORD

T. _____ R. _____ M. _____ Coordinates: X _____ Y _____

Corner common to sections _____



= Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed _____
Original monument _____

Original Evidence Found

Year of search _____ by _____
Monument found _____

Bearing Trees

Species _____
Diameter _____
Bearing _____
Distance _____

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:

Evidence of Subsequent Corner Restoration

Year of search _____ By _____
Location filed:
Monument:

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:


Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Location filed:
Monument:

Index No. E5

CASS COUNTY LAND CORNER RECORD

T. 141 R. 28 M. 5TH Coordinates: X NE 7 Y 56, 7, 8
Corner common to sections 56, 7, 8



EXISTING SURVEYS

Original Government Survey

Year surveyed 1874

Original monument Post

Bearing Trees		
Species	W. PINE	W. PINE
Diameter	<u>26"</u>	<u>30"</u>
Bearing	<u>N75E</u>	<u>S56E</u>
Distance	<u>10 LKS</u>	<u>36 LKS</u>

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species	Diameter	Bearing	Distance

O = Corner

Subsequent Corner Restoration

Year surveyed 1915 By JOHN CURO

Location filed COUNTY SURVEY RECORD BOOK 8 P. 169-177

Monument FIND OLD CORNER BITS SET 2 1/2 X 48" IRON

1915 - Baldwin - microfilm - roll 105 BK 60 P. 92, 110
Find post reestablished by someone

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>W. PINE STUB</u>	<u>30"</u>	<u>N6E</u>	<u>57.10'</u>

Evidence of Subsequent Corner Restoration

Year of search 1918 By GLD

FILED AT: SECRETARY OF STATE FIND 2" GALV.
I.P. AND OLD CORNER BITS: 30" W. PINE STUMP N 29E 10 LKS,
30" W. PINE STUMP S 56E 44 LKS, 30" W. PINE STUMP
S 75 W 67 LKS, SET 2 X 36" I.P. W/ BRASS CAP 7 1/4 IN. R 28 IN.

56 | 55
57 | 58

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>R. OAK</u>	<u>6"</u>	<u>N 23 1/4 E</u>	<u>62 LKS</u>
<u>POP LAR</u>	<u>6"</u>	<u>S 9 1/4 E</u>	<u>16 LKS</u>
<u>R. OAK</u>	<u>5"</u>	<u>S 39 W</u>	<u>82 LKS</u>
<u>R. OAK</u>	<u>10"</u>	<u>N 1 1/4 W</u>	<u>272 LKS</u>

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____
Filed at _____ Date _____