


Index No. 515

CASS COUNTY LAND CORNER RECORD

T. 141 R. 29 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
N 1/4 15 Corner common to sections 10, 15



EXISTING SURVEYS

Original Government Survey  
Year surveyed 1873  
Original monument POST

Original Evidence Found  
Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees  
Species W. PINE W. PINE  
Diameter 20" 15"  
Bearing N37E N38W  
Distance 33 LKS 55 LKS

Original Bearing Trees Found  
Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Subsequent Corner Restoration  
Year surveyed 1918 By GLO  
Location filed SEC. OF STATE  
Monument FIND BOTH GOVT B.T. STUMPS SET 1x36" I.P.  
W/BRASS CAP 14 S10  
14 S15  
1918

Evidence of Subsequent Corner Restoration  
Year of search 1980 By GARY STEVENSON  
Found GLO monument bent over.  
Set 2 1/2 x 3/4" galvanized iron pipe with  
marked brass cap 0.6' above ground.

Bearing Trees, Reference Objects  
Species W. OAK POPLAR  
Diameter 14" 6"  
Bearing N16-15E S40-15E  
Distance 218 LKS 71 LKS

Bearing Trees, Reference Objects  
Pine stump B. Oak W. Oak W. Oak  
24" 12" 7" 24"  
N 38 W S 33 W N 64 E N 16 1/4 E  
36.00' 18.65' 24.71' 143.28'

Subsequent Corner Restoration  
Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found  
Year of search \_\_\_\_\_ By \_\_\_\_\_  
CERTIFICATE - GARY STEVENSON - 1981  
Doc. # 200992

Remonumentation certificate prepared \_\_\_\_\_  
Filed at \_\_\_\_\_

By \_\_\_\_\_  
Date \_\_\_\_\_