

Index No. _____

CASS COUNTY LAND CORNER RECORD

T. _____ R. _____ M. _____ Coordinates: X _____ Y _____

Corner common to sections _____



= Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed _____
Original monument _____

Original Evidence Found

Year of search _____ by _____
Monument found _____

Bearing Trees

Species _____
Diameter _____
Bearing _____
Distance _____

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:

Evidence of Subsequent Corner Restoration

Year of search _____ By _____
Location filed:
Monument:

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:


Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Location filed:
Monument:

Index No. E13

CASS COUNTY LAND CORNER RECORD

T. 141 R. 30 M. 5TH Coordinates: X _____ Y _____
NE 9 Corner common to sections 3, 4, 9, 10



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing Trees			
	W. Pine	PINE	POPLAR	POPLAR
Diameter	<u>36"</u>	<u>10"</u>	<u>3"</u>	<u>3"</u>
Bearing	<u>N76E</u>	<u>S60W</u>	<u>N60 1/2 W</u>	<u>N63E</u>
Distance	<u>160 LKS</u>	<u>166 LKS</u>	<u>34 LKS</u>	<u>80 LKS</u>

Species	Original Bearing Trees Found			
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed _____ By ROAD SURVEY
Location filed COUNTY BOOK 'D' P. 104-105
Monument IRON MONUMENT

Evidence of Subsequent Corner Restoration

Year of search 1917 By GLO
FIND SW. BIT STUMP SET 1836' 1A W /
BRASS CAP. T141N R30W
54 | 53
59 | 510
1917

Bearing Trees, Reference Objects

Species				
Diameter				
Bearing				
Distance				

Bearing Trees, Reference Objects

POPLAR	POPLAR	P. OAK	POPLAR
<u>8"</u>	<u>8"</u>	<u>8"</u>	<u>8"</u>
<u>N1 1/4 E</u>	<u>S54E</u>	<u>S33 1/2 W</u>	<u>N53 3/4 W</u>
<u>75 LKS</u>	<u>58 LKS</u>	<u>77 LKS</u>	<u>45 LKS</u>

E-13

Subsequent Corner Restoration

Year surveyed 8/01 By CCSO
Location filed P.L.C. #2001.037
Monument Found PK nail at 22, (May have been 0+00 for CR#124). Witness as follows:

- 6" W. Oak N36°E, 56.74'*
- 14" N. Pine N58°W, 89.90'*
- P. Pole S38°W, 125.53'*
- Tel. Pole S18°E, 101.42'*
- *distance to double head nail

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____