


Index No. E 25

CASS COUNTY LAND CORNER RECORD

T. 141 R. 30 M. 5th Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 1/2 Corner common to sections 1, 12 and 6, 7-14-29



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873

Original monument Post

Species	Bearing	Tree	Distance
<u>R. OAK</u>	<u>S 1/2 E</u>	<u>MAPLE</u>	<u>14"</u>
<u>R. OAK</u>	<u>N 63 W</u>	<u>R. OAK</u>	<u>15 LKS</u>
<u>R. OAK</u>	<u>S 48 W</u>	<u>R. OAK</u>	<u>18"</u>
<u>R. OAK</u>	<u>S 82 E</u>	<u>R. OAK</u>	<u>20"</u>
<u>R. OAK</u>	<u>N 30 1/2 E</u>	<u>R. OAK</u>	<u>33 LKS</u>
<u>R. OAK</u>	<u>N 63 W</u>	<u>R. OAK</u>	<u>15 LKS</u>
<u>R. OAK</u>	<u>S 48 W</u>	<u>R. OAK</u>	<u>33 LKS</u>
<u>R. OAK</u>	<u>S 82 E</u>	<u>R. OAK</u>	<u>34 LKS</u>

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Monument found \_\_\_\_\_

Original Bearing Trees Found

Species \_\_\_\_\_

Diameter \_\_\_\_\_

Bearing \_\_\_\_\_

Distance \_\_\_\_\_

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By ROAD SURVEY

Location filed COUNTY BOOK D' P104-105

Monument IRON MONUMENT

Evidence of Subsequent Corner Restoration

Year of search 1917 By GLO

TWO OLD WOOD STAKE AND NE, SE & SW BT. STAMPS.

SET 2x36" I.P. W/BRASS CAP

<u>T14R N</u>	<u>R30W R29W</u>
<u>51</u>	<u>56</u>
<u>512</u>	<u>57</u>

Bearing Trees, Reference Objects

Species \_\_\_\_\_

Diameter \_\_\_\_\_

Bearing \_\_\_\_\_

Distance \_\_\_\_\_

Bearing Trees, Reference Objects 1917

Species	Diameter	Bearing	Distance
<u>W. OAK</u>	<u>12"</u>	<u>N 79 E</u>	<u>99 LKS</u>
<u>W. OAK</u>	<u>14"</u>	<u>S 55 1/2 E</u>	<u>86 LKS</u>
<u>BASSWOOD</u>	<u>8"</u>	<u>S 69 1/2 W</u>	<u>125 LKS</u>
<u>BASSWOOD</u>	<u>10"</u>	<u>N 37 1/2 W</u>	<u>96 LKS</u>

E-25

Subsequent Corner Restoration

Year surveyed 1935 By USFS, McKinley

Location filed USFS Cass Lake

Monument Found monument and 3 GLO BT'S.

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

CERTIFICATE - BUTLER SMITH - HWY ENGINEER - 1921

1938 - MNDOT found brass cap monument and GLO and 1921 witness

1941 post construction MNDOT lists the following witnesses.

<u>5" Basswood</u>	<u>NE</u>	<u>111.8'</u>
<u>8" Basswood</u>	<u>NW</u>	<u>91.5'</u>
<u>RCP West</u>	<u>SW</u>	<u>55.6' "X"</u>
<u>RCP East</u>	<u>SE</u>	<u>57.5' "X"</u>

CERTIFICATE - WALT CURR - 1981

Doc. # 262633

Found 1/2 bolt with 1" sq head on top of 1"x36" brass cap monument, push it down, set 2"x24" brass cap monument on top.

Ties: 12" Norway Pine N10W 69.35'; 7" Red Oak N30E 101.10'; 7" Jack Pine S40E 91.03'; 7" Norway Pine S38W 70.64'.

9/03 - NLSEM set concrete nail from 1921 witness trees, over strong magnetic signal. A Capl was filed.

Remonumentation certificate prepared #480060

Filed at CCRO

By #16089

Date 2/12/04