Index No. 22-3

CASS COUNTY LAND CORNER RECORD

T. 141 R. 30 M. 5TH Coordinates: X _____ Y _____

M C# 35 Corner common to sections 31



EXISTING SURVEYS

Original Government Survey

Year surveyed 1863

Original monument Post

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species	W. Pine	W. Pine		
Diameter	12"	14"		
Bearing	N60E	57W		
Distance	7 LKS	13 LKS		

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1915 By John Curo

Location filed microfilm - roll 105 BK 63 P. 6

Monument Fnd 2" Capped I.P. and stumps of Both orig B.T.S I.P. is in cement

Evidence of Subsequent Corner Restoration

Year of search 1911 By John Curo

County Book "A" P. 385

Pull wood hub previously established - set 2"x48" I.P. capped set in cement - Both B.T. Stumps Check for course & dist

Bearing Trees, Reference Objects

Species				
Diameter				
Bearing				
Distance				

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Certificate - Jim Nielsen - Minn DOT 1983

1989 Certificate - David Landecker Doc. # 311860 Found 2" capped iron pipe. Ties: 13" Spruce N 65 E 52.20'; 9" Red Oak S 78 E 15.48'; 16" Red Oak S 34 W 9.74'.

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____