


T. 141 R. 31 M. 5TH Coordinates: X _____ Y _____
NE 1 Corner common to sections 1 AND 6-141-30 AND 31-142-30
AND 36-142-31



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
 Original monument POST

Original Evidence Found

Year of search _____ By _____
 Monument found _____

Species	Bearing Trees			
	W. PINE	W. PINE	W. PINE	W. PINE
Diameter	<u>14"</u>	<u>8"</u>	<u>10"</u>	<u>7"</u>
Bearing	<u>N33E</u>	<u>N15W</u>	<u>S48 1/2 W</u>	<u>S80E</u>
Distance	<u>36 LKS</u>	<u>43 LKS</u>	<u>87 LKS</u>	<u>37 LKS</u>

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1911 By HARRY S. TODD
 Location filed COUNTY SURVEY RECORD BOOK "A" P 382-383
 Monument Found here previously set by Todd from old
Govt B.T.S SET 2X48" CAPRED CALV. I.P.
1916 E.B. Horst, Book 16" P. 523 From I.M. SET BY (WOOD
also on microfilm - roll 115 BK 80 P. 40

Evidence of Subsequent Corner Restoration

Year of search 1911 By Harry Todd
microfilm - roll 115 BK 73 P. 21
Found all B.T. stumps - set corner.
1917 - Horst - microfilm - roll 115 BK 77 P. 96
Section line diagram shows 2 1/2 X 48' I.P.

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

A25

Subsequent Corner Restoration

Year surveyed 1917 By GLD
 Location filed _____
 Monument End 2" I.P. w/ cap - and orig B.T. : 14"
w. pine S80E 37 LKS
set 3x36" I.P. w/ brass cap
8" N. Pine N38E 142 LKS
6" N. Pine S77E 188 LKS
5" W. oak S77 1/4 W 282 LKS
6" W. oak N75 1/2 W 93 LKS

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
PLAT - PLAT OF SURVEY
R.F. SCHNEIDER 1915
march 1922, Twp order shows no survey

1984 - T. Freeman and USFS C. Krause, G. Braune,
J. Allison End 2" x 28" I.P. bent south -
straightened - set down 0.8' Three GLD
ties: 21" N. Pine N10E 93.55'
19" N. Pine S76E 124.3'
15" W. oak N73W 61.4'
New tie: 17" N. Pine S49W 88.2'
Corner in E of N-S Road