


Index No. C13

CASS COUNTY LAND CORNER RECORD

T. 141 R. 31 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
E1/4 4 Corner common to sections 3,4



EXISTING SURVEYS

**Original Government Survey**  
 Year surveyed 1873  
 Original monument POST

**Bearing Trees**  
 Species POPLAR POPLAR  
 Diameter 7" 4"  
 Bearing S74E N71W  
 Distance 115 LKS 127 LKS

**Original Evidence Found**  
 Year of search \_\_\_\_\_ By \_\_\_\_\_  
 Monument found \_\_\_\_\_

**Original Bearing Trees Found**  
 Species \_\_\_\_\_  
 Diameter \_\_\_\_\_  
 Bearing \_\_\_\_\_  
 Distance \_\_\_\_\_

**Subsequent Corner Restoration**  
 Year surveyed 1925 By JOHN GREENE  
 Location filed COUNTY RESURVEY "E-81"  
 Monument IRON MONUMENT  
1942, JOHN CURR, BOOK "D" P. 296-297 TIES

**Evidence of Subsequent Corner Restoration**  
 Year of search 1929 By Minn Hurt Dept.  
R/W map in Recorder's office - Walker to Atkey  
2" iron pipe & cap in place

**Bearing Trees, Reference Objects**  
 Species W. PINE N. PINE  
 Diameter 14" 12"  
 Bearing N56W N52E  
 Distance 18.80' 21.50'  
1942 TIES

**Bearing Trees, Reference Objects**  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**Subsequent Corner Restoration**  
 Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
 Location filed \_\_\_\_\_  
 Monument \_\_\_\_\_

**Evidence of Subsequent Corner Restoration Found**  
 Year of search \_\_\_\_\_ By \_\_\_\_\_  
CERTIFICATE - PETER MEYER - 1962  
Found 2" iron pipe; 14" W. Pine N50W  
18.80' now 17"; N. Pine N52E 21.50' now  
15". Set 6"x5" cylindrical concrete  
monument capped with 3" stamped bronze  
tablet. Ties: 17" Red Pine N87W 25.7'; 17"  
Red Pine N50E 21.95'; 4x4x72" Cedar  
post S81W 5.3'.  
1977 - W. Curr - Certificate of  
survey indicates monument in  
place.

Remonumentation certificate prepared \_\_\_\_\_  
Filed at \_\_\_\_\_

By \_\_\_\_\_  
Date \_\_\_\_\_