Index No. C 25

CASS COUNTY LAND CORNER RECORD

T. 141 R. 31 M. 5TH Coordinates: X _____ Y _____

E1/4 1 Corner common to sections LAND 6-141-30



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873

Original monument POST

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species	ASPEN	R.OAK		
Diameter	10"	8"		
Bearing	N75E	S2½W		
Distance	41 LKS	296 LKS		

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1917 By E.B. HORST

Location filed COUNTY BOOK "B" P.569

Monument FND 2½ x 48" I.M.

1912- M.A. KEMP FND OLD GOVT BITS: 8" R.OAK (DOWN) S2½W 296 LKS AND (STUMP) ASPEN N75E 41 LKS SET 1" I.P.

Evidence of Subsequent Corner Restoration

Year of search 1917 By GLO

FND 2" GAS PIPE AND STUMPS OF BOTH GOVT BITS. SET 1X36" I.P. W/BRASS CAP 1/4 S1/S6 1917

Bearing Trees, Reference Objects

Species				
Diameter	1917- also on microfilm - roll 115			
Bearing	BK77 P. 95-96			
Distance				

Bearing Trees, Reference Objects

	W.OAK	W.OAK		
	5"	4"		
	N14E	N87½W		
	167 LKS	197 LKS		

Subsequent Corner Restoration

Year surveyed 1911 By Harry Todd

Location filed microfilm - roll 115 BK73 P.21

Monument set corner

1984- T. Freeman: USFS Fnd 2x36" I.P. and 1X36" I.P. (GLO w/cap gone) GLO pipe down 1' and bent S. Both pipes are over common point straightened and reset down 6" also Fnd GLO BIT.: 14" W. oak N14E 110.6'
22" N. pine N64E 148.55'
10" W. oak N29E 57.70'
8" W. oak N68W 119.95'

1999- Landecker & Assoc. - Certificate of Survey indicates found iron monument.

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____