Index No. E 12

CASS COUNTY LAND CORNER RECORD

T. 141 R. 31 M. 5TH Coordinates: X _____ Y _____

E 1/16 Corner common to sections 4, 9



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed _____

Original monument _____

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species _____

Diameter _____

Bearing _____

Distance _____

Original Bearing Trees Found

Species _____

Diameter _____

Bearing _____

Distance _____

Subsequent Corner Restoration

Year surveyed 1929 By Minn Hwy Dept

Location filed R/W map in Recorder's office - Walker to Akeley

Monument 2" iron pipe & cap in place

Evidence of Subsequent Corner Restoration

Year of search 1962 By Pete Meyer

found 2" capped iron pipe. Set 2" x 5' galvanized wrought iron pipe filled with concrete and capped with 3" stamped bronze tablet.

Bearing Trees, Reference Objects

Species _____

Diameter _____

Bearing _____

Distance _____

Bearing Trees, Reference Objects

Oak	R. E. A. Pole
7"	9"
N 36 E	S 89 E
55.25'	45.7'

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

CERTIFICATE - PETE MEYER - 1962

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____