


T. 141 R. 31 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_

NE 10 Corner common to sections 2, 3, 10, 11



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873  
Original monument POST

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Species	Bearing Trees			
	N. PINE	N. PINE	J. PINE	J. PINE
Diameter	10"	14"	6"	9"
Bearing	N27E	N70W	S15E	S34W
Distance	15 LKS	19 LKS	14 LKS	?

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1948 By HAROLD CURD  
Location filed COUNTY BOOK "D" P. 343  
Monument END 2x4" CAPED I.P. PREVIOUSLY ESTABLISHED  
1951, HAROLD CURD, BOOK "D" P. 391 END I.M.

Evidence of Subsequent Corner Restoration

Year of search 1917 By GLO  
END 2" I.P. (NO TIES)  
1906, GLO - END 4" SCRIBED POPLAR POST  
AND BITS: 12" POPLAR N20E 59 LKS, 14" POPLAR S20 1/4 E 48 LKS

Bearing Trees, Reference Objects

Species	R. OAK	R. OAK	R. OAK	R. OAK
Diameter	4"	8"	8"	6"
Bearing	N53-47E	S28-03E	S57-38W	N53-22W
Distance	17.85'	39.75'	27.55'	22.65'

1948 TIES

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1914 By CURD  
Location filed microfilm - roll 115 BX92 P 90-91  
Monument END K.K. Whiteley's 1895 oak  
B.I.S.

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

8" Bl. oak	N19 1/2 E	40.59'	standing dead
7" "	S19 1/4 E	29.70'	stump
12" "	N84 1/2 W	77.55'	
14" "	S77 3/4 W	85.14'	

Set stake. from his notes he said  
corner should be 3.76' N. (20°V) and 30.69'  
egst. chained this end set 2x4x8" galv.  
cap. I.P. in mound