


Index No. E 21

CASS COUNTY LAND CORNER RECORD

T. 141 R. 31 M. 5TH Coordinates: X _____ Y _____
NE 11 Corner common to sections 11R, 111R



EXISTING SURVEYS

Original Government Survey
Year surveyed 1873
Original monument POST

Original Evidence Found
Year of search _____ By _____
Monument found _____

Species		Bearing		Trees	
N. PINE	PINE	N. PINE	N. PINE		
13"	8"	8"	10"		
S60E	S31W	N42E	N67W		
90LKS	70LKS	60LKS	13LKS		

Original Bearing Trees Found
Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration
Year surveyed 1916 By F.F. WILSON
Location filed COUNTY BOOK C P. 111
Monument FIND T.M. SET PREVIOUSLY BY JOHN CURO
1942, JOHN CURO, BOOK D P. 276-277 FIND 2X48" GALV. I.P.
ALSO FIND 2" BRASS CAP SET BY GLO 0.5' EAST

Evidence of Subsequent Corner Restoration
Year of search 1917 By GLO
FIND 2" I.P. W/BRASS CAP SET 2X36" I.P. W/BRASS
CAP. 7.141 N R31W
52/51
511/512
1917

Species		Bearing		Trees, Reference Objects	
W. BIRCH	W. BIRCH	W. OAK	N. PINE		
TRIPLE 5.78"	7"	TWIN 5.6"	8"		
N46-30E	N32-30W	S32-15W	S87-30E		
14.7	31'	33.40'	107'		

1942 TIES

Species		Bearing		Trees, Reference Objects	
OAK	MOUND OF STONE				
3"	2' BASE				
S5-15E	1 1/2' HIGH				
43LKS	W. OF COR.				

E-21

Subsequent Corner Restoration
Year surveyed 1982 By FREEMAN-HUMMERTSCH
Location filed _____
Monument FIND 2 I.P.'S W/BRASS CAPS.

Evidence of Subsequent Corner Restoration Found
Year of search _____ By _____

1914 - Curo microfilm - roll 115 BK 92 P. 83-84
start N. from corner. Find old stake and
old B.T.S set 2X48" galv. capped iron.

1987 - Cass County - USFS - Cert. - Doc #
find both I.P.'s w/caps
FGSP SOUTH 4.0'
7" N. Pine NORTH 26.41' MKd S2BT
4" J. Pine S12W 19.83'
15" N. Pine S26W 43.09 MKd T141 NR31W BT

6/2000 CCSO found & located GLO
monument, 30'± W. of R/R grade.

1989 Certificate - Walter Curo
Doc # 309687