


T. 141 R. 31 M. 5TH Coordinates: X _____ Y _____
NE 12 Corner common to sections 1, 12 AND 6, 7-141-30



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Original Bearing Trees Found

Species	Bearing	Tree	Distance
<u>W. PINE</u>	<u>30"</u>	<u>Y. PINE</u>	<u>24"</u>
<u>30"</u>	<u>30"</u>	<u>24"</u>	<u>24"</u>
<u>N12 1/2 E</u>	<u>N1W</u>	<u>S29 1/2 W</u>	<u>S14E</u>
<u>71 LKS</u>	<u>32 LKS</u>	<u>166 LKS</u>	<u>82 LKS</u>

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1917 By E & B. HORST
Location filed COUNTY BOOK B' P. 569
Monument FRD WOOD POST AND OLD GALT BITS: SNAG
30" W. PINE N12-30E 71 LKS, AND STUMP: 30" W. PINE
N1W 32 LKS, 24" Y. PINE S29-30W 166 LKS
1916. F.F. WILSON - BOOK C' P. 116. FRD T.M. SET BY GALT

Evidence of Subsequent Corner Restoration

Year of search 1917 By GLO
FRD NE & NW GALT BITS. SET 2X36" I.P. W/
BRASS CAP. T141N
R31W 51 56 R30W
512 57
1917

Bearing Trees, Reference Objects

Species _____
Diameter 1917 - HORST - also on micro film - roll 115
Bearing AK 77 P. 94-95
Distance _____

Bearing Trees, Reference Objects

N. PINE	W. OAK	R. OAK	W. OAK
<u>5"</u>	<u>6"</u>	<u>6"</u>	<u>4"</u>
<u>N 60 E</u>	<u>S23 1/2 E</u>	<u>S19 1/2 W</u>	<u>N59 W</u>
<u>74 LKS</u>	<u>78 LKS</u>	<u>153 LKS</u>	<u>51 LKS</u>

E-25

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Certificate - Stevenson - 1903 (County Surveyor)
Doc. # 268429
Found GLO monument down 3' in Hwy. 200.
Set County cast iron monument over
Found brass cap. Ties: 5" N. Pine N64W
140.30'; 6" N. Pine N35W 80.10'; 6" W. Oak
N62E 114.70'; 7" W. Oak S61E 112.32';
10" W. Pine S58E 93.77'; 7" N. Pine S43W
84.38'; 6" N. Pine S77W 188.95'.