Index No. L2

# CASS COUNTY LAND CORNER RECORD

T. 141 R. 31 M. 5TH Coordinates: X _____ Y _____

C.W. 1/16 Corner common to sections 18




O = Corner

## EXISTING SURVEYS

### Original Government Survey

Year surveyed _____

Original monument _____

### Original Evidence Found

Year of search _____ By _____

Monument found _____

### Bearing Trees

Species _____

Diameter _____

Bearing _____

Distance _____

### Original Bearing Trees Found

Species _____

Diameter _____

Bearing _____

Distance _____

### Subsequent Corner Restoration

Year surveyed 1929 By Minn. Hwy Dept.

Location filed R/W map in Recorder's office - Walker to Akeley

Monument 1 1/2" iron pipe in place

### Evidence of Subsequent Corner Restoration

Year of search 1962 By Pete Meyer

Found 1 1/2" iron pipe. Set 6" x 5' cylindrical concrete monument with 3" stamped bronze tablet.

### Bearing Trees, Reference Objects

Species _____

Diameter _____

Bearing _____

Distance _____

### Bearing Trees, Reference Objects

| | |
|---|---|
| J. Pine | Oak |
| 9" | 5" |
| S43W | N49E |
| 53.0' | 9.0' |

### Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

### Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

CERTIFICATE - PETE MEYER - 1962

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____