


Index No. N 9

CASS COUNTY LAND CORNER RECORD

T. 141 R. 31 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 20 Corner common to sections 16, 17, 20, 21



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873  
Original monument POST

Species	Bearing	Trees	
<u>N. PINE</u>	<u>J. PINE</u>	<u>N. PINE</u>	<u>N. PINE</u>
<u>6"</u>	<u>9"</u>	<u>10"</u>	<u>6"</u>
<u>N15W</u>	<u>S60W</u>	<u>N60E</u>	<u>S54E</u>
<u>15 LKS</u>	<u>9 LKS</u>	<u>12 LKS</u>	<u>20 LKS</u>

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1992 By TERRY L. FREEMAN  
Location filed \_\_\_\_\_  
Monument Found remains of all 4 original Pine stumps. Set 2" x 48" iron pipe with brass cap.  
1995 Corner position is SAE 32.35'.

Evidence of Subsequent Corner Restoration

Year of search \_\_\_\_\_ By \_\_\_\_\_

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>Red Oak</u>	<u>6"</u>	<u>N 85 W</u>	<u>27.11'</u>
<u>Burr Oak</u>	<u>7"</u>	<u>S 10 W</u>	<u>26.38'</u>
_____	_____	_____	_____
_____	_____	_____	_____

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

1992 Certificate - Terry L. Freeman  
Doc. # 343557

Remonumentation certificate prepared \_\_\_\_\_

By \_\_\_\_\_

Filed at \_\_\_\_\_

Date \_\_\_\_\_