


Index No. R 25

CASS COUNTY LAND CORNER RECORD

T. 141 R. 31 M. 5TH Coordinates: X _____ Y _____
NE RS Corner common to sections 24, 25 AND 19, 30 - 141 - 30



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing Trees			
	TAM.	TAM.	TAM.	TAM.
Diameter	5"	4"	3"	3"
Bearing	N11E	N35 1/2 W	S64W	S62 1/2 E
Distance	54 LKS	34 5 LKS	10 LKS	15 LKS

Original Bearing Trees Found

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration

Year surveyed 1922 By E. B. Horst
Location filed COUNTY RESURVEY "E-38"
Monument IRON MONUMENT - GOUT B.T.S.
1921, E. B. HORST, COUNTY RESURVEY PLAT "E-53" I.M.
1920, E. B. HORST, BOOK "C" P. 464 FND CORNER P. 466, FND
NE B.T.; ORIG. POST SET 2 1/2 x 30" CAPPED I.P.
also on microfilm - roll 115 BK 80 P. 141
Bearing Trees, Reference Objects

Evidence of Subsequent Corner Restoration

Year of search 1921 By State Hist Dept
R/W Map in Records Office
Corner on E of Road

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
1989 Certificate - David Landecker
Doc. # 310683
Set 2" x 24" iron monument with brass
cap. Concrete monument with brass
tablet GPS 18 S1°32'47" W 39.63'; 9" W.
Pine N42E 66.23'; 7" Maple S25E 85.98';
9" Red Oak S70W 168.75'; 10" Red Oak
N84W 153.49'.

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____