


Index No. V 10-11

CASS COUNTY LAND CORNER RECORD

T. 141 R. 31 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
MC # 35 Corner common to sections 28, 33



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873  
Original monument POST

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees

Species	<u>N. PINE</u>	_____	_____
Diameter	<u>24"</u>	_____	_____
Bearing	<u>SOUTH</u>	_____	_____
Distance	<u>36 LKS</u>	_____	_____

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 9/61 By USFS R.H.M.  
Location filed USFS Book pg. 65  
Monument Found remains of large pine stump and piece of wood.

Evidence of Subsequent Corner Restoration

Year of search 5/2005 By CCSO  
Found remains of Pine stump, Set Alum. Co. Monument, 11'± from Lake on East side of point.

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Bearing Trees, Reference Objects

<u>1P in stump</u>	<u>W. Pine</u>	<u>W. Pine</u>
	<u>19"</u>	<u>25"</u>
<u>South</u>	<u>S 56°W</u>	<u>N 46°W</u>
<u>24.50'</u>	<u>18.30'*</u>	<u>14.62'*</u>

\*distance to double head nail

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Remonumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
Filed at \_\_\_\_\_ Date \_\_\_\_\_