Index No. V 11-12

CASS COUNTY LAND CORNER RECORD

T. 141 R. 31 M. 5TH Coordinates: X _____ Y _____

m C# 34 Corner common to sections 28, 33



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873

Original monument Post

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species	N. Pine	N. Pine
Diameter	30"	24"
Bearing	S35E	N60E
Distance	18 LKS	43 LKS

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1920 By E. B. Horst

Location filed microfilm-roll 115 BK 80 P.146

Monument Fnd NE B.T. - Set corner

Evidence of Subsequent Corner Restoration

Year of search 1985 Feb 28 By Freeman - Hummitzsch

Fnd possible B.T. stumps (NE-axe mark)

put CCLD tag on 4 sided-blazed Birch for approx. corner.

Bearing Trees, Reference Objects

Species	Poplar			
Diameter	12			
Bearing	S26-27W			
Distance	17.2'			

Bearing Trees, Reference Objects

V-11, 12

Subsequent Corner Restoration

Year surveyed 9/61 By USFS R.H.M.

Location filed USFS Book, pg 64

Monument Found 2 large pine stumps which fit Lake shore. NE stump has flat axe blaze facing cor. where BT should be.

5/2005 CCSO found remains of stumps, NE stump blaze still evident. Birch with tag down by beaver. Set Alum. Co. Monument from stumps, 10'± to Lake.

1P in Stump	N 46°E	29.24'
10" B. Oak	S 74°E	28.28'*
20" N. Pine	S 17°W	70.68'*

*distance to double head nail

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____