


Index No. A 15

CASS COUNTY LAND CORNER RECORD

T. 142 R. 26 M. 5TH Coordinates: X _____ Y _____
N 1/4 3 Corner common to sections 3 AND 34-143-26



0 = Corner

EXISTING SURVEYS

Original Government Survey
Year surveyed 1872
Original monument POST

Original Evidence Found
Year of search _____ By _____
Monument found _____

Bearing Trees
Species N. PINE FIR
Diameter 14" 6"
Bearing 55W N18W
Distance 5LKS 4LKS

Original Bearing Trees Found
Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration
Year surveyed 1915 By JOHN GREENE
Location filed COUNTY BOOK B P 572-533
Monument TWO STUMPS OF OLD CORN BITS: 14" N. PINE
55W 5LKS., 6" FIR N18W 4LKS.

Evidence of Subsequent Corner Restoration Found
Year of search 1916 By HORST
microf. film - roll 105 BK 68 P. 25-26
set corner proportionally - 2633.3' E & W
set 50d spike

Bearing Trees, Reference Objects
Species BIRCH W. PINE
Diameter 18" 7"
Bearing N40E S40W
Distance 82.2' 84.9'

Bearing Trees, Reference Objects
w. Pine stump w. Pine stump
14" 14"
SW NW
9.5' 11.9'

Subsequent Corner Restoration
Year surveyed 1987 By Gary Stevenson
Location filed Corner Certificate - Doc # 295272
Monument set 2" x 48" I.P. with marked brass cap
from evidence of 1915 survey, ± 28' W. of
powerline.
9" oak S70°E 97.35'
10" Birch S55°W 59.05'
12" Birch N80°W 59.01'
8' steel sign post North and East 51.0'

Evidence of Subsequent Corner Restoration Found
Year of search _____ By _____
Certificate - Gary Stevenson - 1987

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____