


T. 142 R. 26 M. 5TH Coordinates: X _____ Y _____
NE 8 Corner common to sections 4, 5, 8, 9



EXISTING SURVEYS

Original Government Survey

Year surveyed 1872

Original monument POST

Species	Bearing	Trees	
<u>FIR</u>	<u>FIR</u>	<u>FIR</u>	<u>IRONWOOD</u>
<u>10"</u>	<u>10"</u>	<u>8"</u>	<u>6"</u>
<u>N42W</u>	<u>N14E</u>	<u>S16E</u>	<u>S34W</u>
<u>13 LKS</u>	<u>14 LKS</u>	<u>8 LKS</u>	<u>23 LKS</u>

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species _____

Diameter _____

Bearing _____

Distance _____

Subsequent Corner Restoration

Year surveyed 1920 By JAMES FLYNN

Location filed COUNTY BOOK "C" P. 387

Monument END OLD GOVT BITS! DOWN - FIR N42W
13 LKS, STUMP FIR S16E 8 LKS SET 2 1/2" x 30"
IRON MONUMENT COUNTY RESURVEY 1920 "E-2"

Evidence of Subsequent Corner Restoration

Year of search 1963 By Bill OKerman

Corner Certificate

End 2" I.P. set in 1920
set 2" x 60" I.P. w/cap

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>LINE STUMP</u>	<u>8"</u>	<u>S30E</u>	<u>23.4'</u>

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>oak</u>	<u>7"</u>	<u>S38W</u>	<u>8.7'</u>
<u>oak</u>	<u>6"</u>	<u>S60E</u>	<u>3.7'</u>
<u>Birch</u>	<u>6"</u>	<u>N65W</u>	<u>17.7'</u>
<u>Birch</u>	<u>5"</u>	<u>N46W</u>	<u>19.8'</u>

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

CERTIFICATE - OKERMAN - 1963