Index No. N 17

CASS COUNTY LAND CORNER RECORD

T. 142 R. 26 M. 5TH Coordinates: X _____ Y _____

NE 22 Corner common to sections 14,15,22,23



EXISTING SURVEYS

Original Government Survey

Year surveyed 1872

Original monument Post

Bearing Trees

Species	MAPLE	MAPLE	MAPLE	W. PINE
Diameter	6"	8"	10"	36"
Bearing	N80W	S57W	S60E	N8E
Distance	7 LKS	13 LKS	33 LKS	23 LKS

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1/24/85 By Freeman - Hummitzsch

Location filed

Monument Fnd concrete mon. USFS and USFS ties (below)

Bearing Trees, Reference Objects

Species	OAK	OAK	OAK	ROCK
Diameter	8"	8"	8"	3x3'x6'
Bearing	N69W	N58E	S1E	S20W
Distance	48.9'	9.0'	78.7'	55.0

Evidence of Subsequent Corner Restoration

Year of search 1963 By Bill Okerman

Corner Certificate

Fnd decayed stump of W. Pine N8E, also very old squared, scribed post

Set 6"x60" Concrete Cylinder

Bearing Trees, Reference Objects

OAK	OAK	ROCK	OAK
6"	6"	3x3x6"	6"
N69W	N58E	S20W	S1E
48.9'	9.0'	55.0' w/ X"	78.7'

Subsequent Corner Restoration N-17

Year surveyed _____ By _____

Location filed

Monument

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

CERTIFICATE - OKERMAN - 1963

1997, June, LaVerne Luelling, Found & accepted the U.S.D.A. F.S. brony capped concrete mon. as a perpetuation of Gen. Land Office Corner position. Ties: Oak, 0.230m N58E, 2.714m; Oak, 0.206m, S03E, 23.946m; Steel Sign post, E, 0.562m; Oak, 0.218m, N69W, 14.946m.

Cert. Filed: Dec. 8, 1997; Doc. #395061

Aug 2003 L. Luelling # 16089
Cert. of Surv. shows Mon Found

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____