


T. 142 R. 26 M. 5TH Coordinates: X _____ Y _____
NE 25 Corner common to sections 24, 25 and 19, 30 - 142 - 25



EXISTING SURVEYS

Original Government Survey

Year surveyed 1871
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees

Species	<u>W. PINE</u>	<u>FIR</u>	<u>BIRCH</u>	<u>W. PINE</u>
Diameter	<u>20"</u>	<u>6"</u>	<u>4"</u>	<u>24"</u>
Bearing	<u>S44W</u>	<u>N70W</u>	<u>N25E</u>	<u>S50E</u>
Distance	<u>14 LKS</u>	<u>28 LKS</u>	<u>21 LKS</u>	<u>18 LKS</u>

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration

Year of search 1997 By Laverne Leuelling
Set Galvanized steel pipe with a brass
cap as a perpetuation of the "lost"
position established by Schneider.
Cert. Filed: June 1, 1998; Doc. 400504

Bearing Trees, Reference Objects

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Bearing Trees, Reference Objects

<u>Norway Pine</u>	<u>Norway Pine</u>	<u>White Oak</u>	<u>Norway Pine</u>
<u>0.460m</u>	<u>0.396m</u>	<u>0.302m</u>	<u>0.391m</u>
<u>N59W</u>	<u>N79E</u>	<u>N72E</u>	<u>N33E</u>
<u>26.496m</u>	<u>6.920m</u>	<u>4.322m</u>	<u>11.159m</u>

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____