


Index No. T-U 13

CASS COUNTY LAND CORNER RECORD

T. 142 R. 26 M. 5th Coordinates: X _____ Y _____
MC# 30 Corner common to sections 27, 28



○ = Corner

EXISTING SURVEYS

Original Government Survey
 Year surveyed 1872
 Original monument lost

Original Evidence Found
 Year of search _____ By _____
 Monument found _____

Species	Bearing	Tree	Distance
<u>W. Pine</u>	<u>SPRUCE</u>		
<u>6"</u>	<u>10"</u>		
<u>S34W</u>	<u>S24E</u>		
<u>21KS</u>	<u>10KS</u>		

Original Bearing Trees Found
 Species _____
 Diameter _____
 Bearing _____
 Distance _____

Subsequent Corner Restoration
 Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration
 Year of search 1994 11-30 By Lowell Schellack
 Found nothing. On 1-27-95 placed a 2" x 48" dia.
 galvanized iron mon. w/ a 3" dia. brass cap stamped
 to identify the corner - 14" above ground.
 3-21-95 Cert. filed by Lowell Schellack, RLS 15572.
 Doc # 3165505

Bearing Trees, Reference Objects
 Species _____
 Diameter _____
 Bearing _____
 Distance _____

Bearing Trees, Reference Objects

Species	Bearing	Distance
<u>DBL Red Oak</u>	<u>Birch</u>	<u>Maple</u>
<u>8"</u>	<u>5"</u>	<u>10"</u>
<u>N53E</u>	<u>N69E</u>	<u>S27E</u>
<u>31.10</u>	<u>28.54</u>	<u>54.11</u>

Subsequent Corner Restoration
 Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration Found
 Year of search _____ By _____

Remonumentation certificate prepared _____ By _____
 Filed at _____ Date _____