


Index No. V 11

CASS COUNTY LAND CORNER RECORD

T. 14R R. 27 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
N 1/4 33 Corner common to sections 28, 33



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873

Original monument Post

Species	Bearing	Trees
<u>POPULAR</u>	<u>POPULAR</u>	
Diameter <u>4"</u>	<u>4"</u>	
Bearing <u>S32W</u>	<u>N75E</u>	
Distance <u>28 LKS</u>	<u>10 LKS</u>	

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Monument found \_\_\_\_\_

Original Bearing Trees Found

Species	Bearing	Distance
_____	_____	_____
_____	_____	_____
_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1917 By J.H. FLYNN

Location filed COUNTY BOOK B P 596-597

Monument FIND OLD GOVT B.T: 10" POPULAR S33W  
28 LKS

Evidence of Subsequent Corner Restoration

Year of search 1919 By GLD

FIND DECAYED WOOD STAKE SET 1x36" I.P. W/ BRASS CAP

1/4 S28  
S33  
1919

Bearing Trees, Reference Objects

Species	Bearing	Distance
<u>J. PINE</u>	<u>ASPEN</u>	
Diameter <u>10"</u>	<u>6"</u>	
Bearing <u>N0-30E</u>	<u>S7-36W</u>	
Distance <u>44.5'</u>	<u>35'</u>	

Bearing Trees, Reference Objects

Species	Bearing	Distance
<u>R. OAK</u>	<u>J. PINE</u>	
Diameter <u>6"</u>	<u>12"</u>	
Bearing <u>S41 1/4E</u>	<u>N33 1/2W</u>	
Distance <u>44 LKS</u>	<u>60 LKS</u>	

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_

Location filed \_\_\_\_\_

Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Remonumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
Filed at \_\_\_\_\_ Date \_\_\_\_\_