


Index No. _____

CASS COUNTY LAND CORNER RECORD

T. _____ R. _____ M. _____ Coordinates: X _____ Y _____

Corner common to sections _____



= Corner

EXISTING SURVEYS

Original Government Survey

Original Evidence Found

Year surveyed _____

Year of search _____ by _____

Original monument _____

Monument found _____

Bearing Trees

Original Bearing Trees Found

Species _____

Species _____

Diameter _____

Diameter _____

Bearing _____

Bearing _____

Distance _____

Distance _____

Subsequent Corner Restoration

Evidence of Subsequent Corner Restoration

Year surveyed _____ By _____

Year of search _____ By _____

Location filed: _____

Location filed: _____

Monument: _____

Monument: _____

S 9 | S10
S16 | S15
1928

Bearing Trees, Reference Objects

Bearing Trees, Reference Objects

Species _____

Species _____

Diameter _____

Diameter _____

Bearing _____

Bearing _____

Distance _____

Distance _____

Subsequent Corner Restoration

Evidence of Subsequent Corner Restoration Found

Year surveyed _____ By _____

Year of search _____ By _____

Location filed: _____

Location filed: _____


Monument: _____

Monument: _____

Index No. J 13

CASS COUNTY LAND CORNER RECORD

T. 142 R. 28 M. 5TH Coordinates: X _____ Y _____
NE 16 Corner common to sections 9, 10, 15, 16



EXISTING SURVEYS

Original Government Survey
 Year surveyed 1874
 Original monument POST

Original Evidence Found
 Year of search _____ By _____
 Monument found _____

Species	Bearing	Trees	Distance
<u>MAPLE</u>	<u>N71E</u>	<u>IRONWOOD</u>	<u>24 LKS</u>
<u>IRONWOOD</u>	<u>N31W</u>	<u>BASSWOOD</u>	<u>18 LKS</u>
<u>BASSWOOD</u>	<u>S56W</u>	<u>BASSWOOD</u>	<u>21 LKS</u>
<u>BASSWOOD</u>	<u>S38E</u>		<u>13 LKS</u>

Species	Bearing	Trees	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration
 Year surveyed 1916 By JOHN CRO
 Location filed COUNTY SURVEY RECORD BOOK B PRRD-242
 Monument FIND OLD GOVT BITS & 6" MAPLE N71E
24 LKS, 5" BASSWOOD S56W 21 LKS AND ROOTS OF IRONWOOD
SET IRON MONUMENT

Evidence of Subsequent Corner Restoration
 Year of search 1928 By GLO
FIND 2" I.P. W/CAP, MARKED COR: T142N R28W
CORNER WAS SET BY COUNTY SURVEYOR S9/S10
FROM ORIG. BITS. S16/S15
1928

Bearing Trees, Reference Objects

Species	Bearing	Trees	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Bearing Trees, Reference Objects

Species	Bearing	Trees	Distance
<u>MAPLE</u>	<u>S18-15E</u>	<u>BASSWOOD</u>	<u>37 LKS</u>
<u>IRONWOOD</u>	<u>S39-15W</u>	<u>ASH</u>	<u>78 LKS</u>
<u>BASSWOOD</u>	<u>N77-45W</u>		<u>287 LKS</u>
<u>ASH</u>			

Subsequent Corner Restoration
 Year surveyed 1916 By H.F. Baldwin
 Location filed microfilm - roll 115 BK 76 P 4
 Monument FIND Maple & 5" Basswood SW
BK 77, PAD set I.M.

Evidence of Subsequent Corner Restoration Found
 Year of search _____ By _____

Remonumentation certificate prepared _____ By _____
 Filed at _____ Date _____