142 R 28 M 574 Coordinates: X N'14 34 Corner common to sections 27,34	Y
$N^{1/4}$ 34 Corner common to sections $\frac{2739}{1}$	
EVIE	TING SURVEYS 34
Original Government Survey	Original Evidence Found
	Year of search By
ar surveyed <u>1874</u> iginal monument <u>fost</u>	Monument found
iginal monument <u>Post</u>	
Bearing Trees	Original Bearing Trees Found O = Corner
pecies N. line Politic	Species
ameter 17" 3"	Diameter
earing <u>1040 w 3 x 3 w</u>	
istance 50 LKS 20 LKS	Distance
Subsequent Corner Restoration	Evidence of Subsequent Corner Restoration
ear surveyed 1928 By GLO	Year of search By
ocation filed SEC. OF STATE	
Monument Set 1436" life w/ BRASS CAP PROPRETIONA	1667.
1/ 52 1/ 535	
1928	2
Bearing Trees, Reference Objects	Bearing Trees, Reference Objects
pecies (V-1)AK ROAK Diameter 6" 3"	
34	H
Digmeter	
Diameter 579-15E NY5W	
Bearing \$79-15E NY56.) Distance 350 LKS (064KS	
Searing S79-15E NY563 Distance 350 LKS LOGLKS Subsequent Corner Restaration	Evidence of Subsequent Corner Restoration Found
Bearing <u>\$79-15E</u> <u>NY5W</u> Distance <u>350 Lks</u> <u>(064ks</u>	
Searing S79-15E NY5W Distance 350 LKS (061KS Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Subsequent Corner Restoration ar surveyed By	
Searing S79-15E NY56. Distance 350 LKS (061KS Subsequent Corner Restaration for surveyed By	
Subsequent Corner Restoration ar surveyed By	