


Index No. V5

CASS COUNTY LAND CORNER RECORD

T. 142 R. 30 M. 5TH Coordinates: X _____ Y _____
NE 31 Corner common to sections 29, 30, 31, 32



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing Trees			
	W. Pine	W. Pine	W. Pine	W. Pine
Diameter	<u>20</u>	<u>18</u>	<u>36</u>	<u>24</u>
Bearing	<u>S63 1/2 E</u>	<u>N57 E</u>	<u>S43 1/2 W</u>	<u>N40 1/2 W</u>
Distance	<u>103 lks</u>	<u>64 lks</u>	<u>96 lks</u>	<u>82 lks</u>

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1918 By GLO
Location filed _____
Monument Set 2" x 36" l.P. w/ Br. Cap at double proportional point - no evidence of original

Evidence of Subsequent Corner Restoration

Year of search Sept. 1911 By _____
Trwp rd order shows no survey

Bearing Trees, Reference Objects

Species Raised mound of stone west
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search 1999 By Landecker & Assoc.
Cert. of Survey shows a GLO BRASS Cap monument found.

Remonumentation certificate prepared _____ By _____
Filed at _____ Date _____