


Index No. C 9

CASS COUNTY LAND CORNER RECORD

T. 142 R. 31 M. 5TH Coordinates: X _____ Y _____
E 1/4 5 Corner common to sections 4, 5



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees
Species y. Pine y. Pine
Diameter 24 20
Bearing S 38 W S 40 E
Distance 15 lks 31 lks

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed 1916 By JOHN CURD
Location filed COUNTY RESURVEY PLAT "E-57"
Monument 2 1/4 x 48" I.M.
1915, CURD, BOOK "C" P 507 FWD STUMP OF GOOD BT!
24" y. Pine S 38 W 15 lks SET STAKE SET I.M.
also on micro film - roll 115 BK 81 P 14, 17, 27, 34

Evidence of Subsequent Corner Restoration

Year of search 1919 By GLD
Fd 3" capped iron pipe and accepted
it as corner - set 1" x 36" Br. Cap along
North side.

Bearing Trees, Reference Objects

Species P. ts Pine stump
Diameter mound orig
Bearing N 1 S S 38 W
Distance _____ 15 lks

Bearing Trees, Reference Objects

W. Oak
16"
S 69 W
332 lks.

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____