


Index No. E 9

CASS COUNTY LAND CORNER RECORD

T. 142 R. 31 M. 574 Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 8 Corner common to sections 4, 5, 8, 9



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873  
Original monument POST

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees

Species B. Oak Y. Pine \_\_\_\_\_  
Diameter 10 20 \_\_\_\_\_  
Bearing S 57 E North \_\_\_\_\_  
Distance 310 lbs 1202 lbs \_\_\_\_\_

Original Bearing Trees Found

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Subsequent Corner Restoration

Year surveyed 1912 By JOHN CURR  
Location filed COUNTY SURVEY RECORD BOOK 'A' P 488-489  
Monument SET 3x3x48" OAK STAKE (RESETTING STAKE  
IN CURR'S PLAT)  
1917, E. B. HORST BOOK 'B' P 521-526 FWD I.M.  
1916, JOHN CURR, COUNTY RESURVEY PLAT 'E-57' 2 1/4 x 48"

Evidence of Subsequent Corner Restoration

Year of search 1927 By JOHN GREENE  
COUNTY RESURVEY PLAT 'E-58' I.M.  
1915, JOHN CURR, BOOK 'E' P 507 FWD STAKE SET I.M.  
also on microf. film - roll 115 BK 81 P. 14-15, 28, 38  
1917 - also on microf. film - roll 115 BK 78 P 113-114  
P. 130 2 1/2 x 48" capped I.M.

Bearing Trees, Reference Objects I.M.

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Bearing Trees, Reference Objects

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Subsequent Corner Restoration

Year surveyed 1925 By Miss Hunt Dept.  
Location filed R/W map in Recorder's Office - Walker to  
Cass Lake  
Monument 2" iron pipe iron cap 379.6' W. of C

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

6/19/01 R. MAIN - USFS - FOUND PART OF  
IRON PIPE IN BOG BETWEEN TH 371 AND  
KABERONA BAY. LOCATOR INDICATES MORE  
IRON BELOW SURFACE.

RESOURCE GRADE SPS = LAT 47° 08' 09.91246"  
LONG 94° 37' 36.47591"

Remonumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
Filed at \_\_\_\_\_ Date \_\_\_\_\_