


T. 143 R. 26 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
E 1/4 19 Corner common to sections 19, 20



O = Corner

EXISTING SURVEYS

**Original Government Survey**

Year surveyed 1872

Original monument Post

**Bearing Trees**

Species	<u>Cedar</u>	<u>Cedar</u>
Diameter	<u>14"</u>	<u>6"</u>
Bearing	<u>S41E</u>	<u>N40W</u>
Distance	<u>7 LKS</u>	<u>8 LKS</u>

**Original Evidence Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_

Monument found \_\_\_\_\_

**Original Bearing Trees Found**

Species	_____	_____
Diameter	_____	_____
Bearing	_____	_____
Distance	_____	_____

**Subsequent Corner Restoration**

Year surveyed 1915 By John Curo

Location filed COUNTY SURVEY RECORD BOOK 'B' P. 81-85

Monument Two Old Goat Spikes And Bits Down - 14"  
CEDAR S41E 7 LKS, 6" CEDAR N40W 8 LKS,  
- also on microfilm - roll 115 BK 71 P. 104

**Evidence of Subsequent Corner Restoration**

Year of search 1986 By Ken Whitehorn

Set 2 1/2" x 40" galvanized iron pipe with magnet at base and 3" stamped brass cap.

**Bearing Trees, Reference Objects**

Species	<u>BALSAM</u>	<u>Asst</u>
Diameter	<u>8"</u>	<u>5"</u>
Bearing	<u>S37-44W</u>	<u>N66 W</u>
Distance	<u>114.10'</u>	<u>108.10'</u>

**Bearing Trees, Reference Objects**

<u>Tamarack</u>	<u>Birch</u>	<u>Poplar</u>
<u>13 1/2"</u>	<u>6"</u>	<u>7 1/2"</u>
<u>N44 W</u>	<u>N65 E</u>	<u>S44 W</u>
<u>39.58'</u>	<u>30.83'</u>	<u>23.83'</u>

**Subsequent Corner Restoration**

Year surveyed \_\_\_\_\_ By \_\_\_\_\_

Location filed \_\_\_\_\_

Monument \_\_\_\_\_

**Evidence of Subsequent Corner Restoration Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_

1986 Certificate - Ken Whitehorn  
Doc # 289674