


T. 143 R. 26 M. 5TH Coordinates: X _____ Y _____
NE 30 Corner common to sections 19, 20, 29, 30



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1872
Original monument lost

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing	Tree	Distance
<u>Fir</u>	<u>S22E</u>	<u>15 LKS</u>	
<u>Spruce</u>	<u>S22W</u>	<u>21 LKS</u>	
<u>Maple</u>	<u>N45E</u>	<u>30 LKS</u>	
<u>W. Pine</u>	<u>N48W</u>	<u>56 LKS</u>	

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1915 By JOHN CURD
Location filed COUNTY SURVEY RECORD BOOK "B" P. 81-85
Monument FIND OLD GOVT B.T.S: 6" MAPLE N45E 30 LKS,
10" SPRUCE S22W 21 LKS SPT corner
- also on microfilm - roll 115 BK 71 P. 98

Evidence of Subsequent Corner Restoration

Year of search 1918 By JAMES FLYNN
BOOK "C" P. 150 FIND OLD GOVT B.T.S: STUMP
5" FIR S22E 15 LKS, STUMP 26" W. PINE N48W
56 LKS. SET IRON MONUMENT. 2 1/2 X 30" W/CAP
COUNTY RESURVEY 1918 "E-3"

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>CEDAR</u>	<u>12"</u>	<u>N61-18E</u>	<u>66.60'</u>
<u>W. OAK</u>	<u>18"</u>	<u>S32E</u>	<u>41.70'</u>
<u>IRONWOOD</u>	<u>6"</u>	<u>S72-30W</u>	<u>47.30'</u>
<u>BASSWOOD</u>	<u>12"</u>	<u>N59-43W</u>	<u>36.20'</u>

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>W. OAK</u>	<u>18"</u>	<u>S35-45E</u>	<u>45'</u>
<u>BASSWOOD</u>	<u>12"</u>	<u>N66W</u>	<u>34'</u>

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
CERTIFICATE - BILL CROEMAN - 1969
Set 2" x 5' galvanized steel pipe filled
with concrete and capped with 3"
stamped brass tablet.
7" W OAK S67E 54.40'
10" W OAK S16W 66.45'
5" W OAK N57W 49.90'
8" Elm N15E 37.50'