

Index No. _____

CASS COUNTY LAND CORNER RECORD

T. _____ R. _____ M. _____ Coordinates: X _____ Y _____

Corner common to sections _____

= Corner

EXISTING SURVEYS

Original Government Survey

Original Evidence Found

Year surveyed _____

Year of search _____ by _____

Original monument _____

Monument found _____

Bearing Trees

Original Bearing Trees Found

Species _____

Species _____

Diameter _____

Diameter _____

Bearing _____

Bearing _____

Distance _____

Distance _____

Subsequent Corner Restoration

Evidence of Subsequent Corner Restoration

Year surveyed _____ By _____

Year of search _____ By _____

Location filed: _____

Location filed: _____

Monument: _____

Monument: _____

Bearing Trees, Reference Objects

Bearing Trees, Reference Objects

Species _____

Species _____

Diameter _____

Diameter _____

Bearing _____

Bearing _____

Distance _____

Distance _____

Subsequent Corner Restoration

Evidence of Subsequent Corner Restoration Found

Year surveyed _____ By _____

Year of search _____ By _____

Location filed: _____

Location filed: _____

Monument: _____

Monument: _____

Certificate of Location of Government Corner filed in Cass County

By _____


Recorders Office as Document _____

Date _____

Index No. V15

CASS COUNTY LAND CORNER RECORD

T. 143 R. 27 M. 5TH Coordinates: X _____ Y _____
N114 34 Corner common to sections 27, 34



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument lost

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing	Trees
<u>Aspen</u>	<u>Tam</u>	
Diameter <u>16"</u>	<u>6"</u>	
Bearing <u>N41W</u>	<u>S5W</u>	
Distance <u>22 LKS</u>	<u>13 LKS</u>	

Original Bearing Trees Found	Species	Diameter	Bearing	Distance
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____
_____	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1915 By JOHN LERO
Location filed COUNTY BOOK B P455-462
Monument SET CORNER PROPORTIONALLY
also on microfilm - roll 115 BK 79 P. 29

Evidence of Subsequent Corner Restoration

Year of search 1998 By NLSEM RLS #16089
Set a 2" x 24" galv. steel pipe w/ brass cap, below road surface.

Bearing Trees, Reference Objects

Species	Bearing	Distance
<u>TAM STUMP DEAD w/ PINE SWAG</u>		
Diameter <u>10"</u>	<u>12"</u>	
Bearing <u>S56E</u>	<u>N38E</u>	
Distance <u>61.80'</u>	<u>97.30'</u>	

Bearing Trees, Reference Objects

Species	Bearing	Distance	Species	Distance
<u>N. Pine</u>	<u>Balsam</u>	<u>N. Pine</u>	<u>Steel</u>	
<u>10"</u>	<u>7"</u>	<u>16"</u>	<u>Sgn Post</u>	
<u>N44°E</u>	<u>S8°E</u>	<u>S15°W</u>	<u>N16°W</u>	
<u>51.73'</u>	<u>74.51'</u>	<u>88.19</u>	<u>35.10'</u>	

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared
Filed at CCRO Doc # 412862

By NLSEM
Date 5/17/99