


T. 143 R. 29 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 6 Corner common to sections 5, 6 AND 31, 32-144-29



EXISTING SURVEYS

**Original Government Survey**

Year surveyed 1873  
Original monument Post

Species	Bearing Trees		
<u>Cedar</u>	<u>Fir</u>	<u>Fir</u>	<u>Cedar</u>
Diameter <u>14"</u>	<u>6"</u>	<u>6"</u>	<u>24"</u>
Bearing <u>N88E</u>	<u>N64W</u>	<u>S63W</u>	<u>S60E</u>
Distance <u>20 LKS</u>	<u>8 LKS</u>	<u>15 LKS</u>	<u>18 LKS</u>

**Original Evidence Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

**Original Bearing Trees Found**

Species	Diameter	Bearing	Distance

**Subsequent Corner Restoration**

Year surveyed 1924 By GLO  
Location filed Sec. of State  
Monument Sct 2x 36" l.p. w/ brass cap proportionally  
T144N R29W  
531 | 532  
56 | 55

**Evidence of Subsequent Corner Restoration**

Year of search 1987 By Gary Stevenson  
Corner Cert. Ficate - Doc # 308485  
Find GLO 2" l.p. w/ brass cap and 1 1924 BT  
and 2 1963 BT's

**Bearing Trees, Reference Objects 1924**

Species	Bearing	Distance
<u>Poplar</u>	<u>7"</u>	<u>N41E</u>
<u>Birch</u>	<u>4"</u>	<u>S42-30E</u>
<u>Birch</u>	<u>6"</u>	<u>S79-30W</u>
<u>Poplar</u>	<u>6"</u>	<u>N49-15W</u>
Distance	<u>146 LKS</u>	<u>23 LKS</u>
		<u>53 LKS</u>
		<u>39 LKS</u>

**Bearing Trees, Reference Objects**

Species	Bearing	Distance
<u>Elm</u>	<u>9"</u>	<u>N68E</u>
<u>Balsam</u>	<u>12"</u>	<u>S8E</u>
<u>Birch snag</u>	<u>12"</u>	<u>S80W</u>
		<u>30.00'</u>
		<u>10.50'</u>
		<u>35.62'</u>
		<u>1924 BT</u>

**Subsequent Corner Restoration**

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

**Evidence of Subsequent Corner Restoration Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_  
CERTIFICATE - BILL OKERMAN - 1963  
Certificate - Gary Stevenson - 1987