Index No. CASS COUNTY LAI	ND CORNER RECORD
T R M Coordinates: X	Y
Corner common to sections	
EXISTII Original Government Survey	NG SURVEYS Original Evidence Found
Year surveyed	Year of search by
Original monument	Monument found
	Á= Corner
Bearing Trees	Original Bearing Trees Found
Species	Species
Diameter	Diameter
Bearing	Bearing
Distance	Distance
Subsequent Corner Restoration	Evidence of Subsequent Corner Restoration
Year surveyed By	
Location filed: Monument:	Location filed: Monument:
Monument:	Monument:
Bearing Trees, Reference Objects	Bearing Trees, Reference Objects
Species	Species
Diameter	Diameter
Bearing	Bearing
Distance	Distance
Subsequent Corner Restoration	Evidence of Subsequent Corner Restoration Found
Year surveyed By	Year of search By
Location filed:	Location filed:
Monument:	Monument:
Certificate of Location of Government Corner filed in Cass County	By
Recorders Office as Document	Date

dex No. Y-2 23 CASS COUNTY L	AND CORNER RECORD
144 B 27 M 57H Coordinates: X	Y
14 4 R. 27 M. 57H Coordinates: X Mc # 17 Corner common to sections 36 AND	31-144-76
	20
	TING SURVEYS
Original Government Survey	Original Evidence Found
ear surveyed 1873	Year of searchBy
Original monument Post	Monument found
	O = Corner
Species Spruce Brich	Original Bearing Trees Found
Species Spruce Brich	Species
Diameter647"	Diameter
Bearing 52-30W 57E	Bearing
Distance 92 Us 120 Us	Distance
Subsequent Corner Restoration	Evidence of Subsequent Corner Restoration
ear surveyed 1937 By 640	Year of search By
ocation filed Sec. of State	
Monument Sct 1x36"11P. w 1 bruss cap MC	
5365	
Ratu Ir	
7/49	70
	Bearing Trees, Reference Objects
Species Tam Ash Diameter 7" 9"	
Diameter 711 917	
ALQUE CEZL	
Bearing <u>N 89E</u>	
Bearing <u>N89E 5.53/4 w</u> Distance <u>253LKS</u> 72LKS	Evidence of Subsequent Corner Restoration Found
Subsequent Corner Restoration Year surveyed By	Evidence of Subsequent Corner Restoration Found Year of searchBy
Bearing N89E S53/4W Distance 253LKS 72LKS Subsequent Corner Restoration Year surveyed By Location filed	· · · · · · · · · · · · · · · · · · ·
Bearing N89E S.53/4W Distance 253LKS 72LKS Subsequent Corner Restoration Year surveyed By Location filed	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Bearing <u>N89E 553/4 w</u> Distance <u>253LKS</u> 72LKS	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·
Subsequent Corner Restoration Year surveyed By	· · · · · · · · · · · · · · · · · · ·