


Index No. J 9

CASS COUNTY LAND CORNER RECORD

T. 144 R. 29 M. 5TH Coordinates: X _____ Y _____
NE 17 Corner common to sections 8, 9, 16, 17



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	<u>W. Pine</u>	<u>W. Pine</u>	<u>Elm</u>	<u>Basswood</u>
Diameter	<u>28"</u>	<u>30"</u>	<u>8"</u>	<u>6"</u>
Bearing	<u>N80E</u>	<u>S39E</u>	<u>S60W</u>	<u>N53W</u>
Distance	<u>79Ls</u>	<u>32Ls</u>	<u>89Ls</u>	<u>103Ls</u>

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1926 By GLO
Location filed Sec. of State
Monument Find NE, SE, & SW B.T. Stumps Set 2x36"
1 1/2" w/ brass cap 714N R29W
SB 159
517 5/6

Evidence of Subsequent Corner Restoration

Year of search _____ By _____

Bearing Trees, Reference Objects 1926

Species	<u>Elm</u>	_____	_____	_____
Diameter	<u>7"</u>	_____	_____	_____
Bearing	<u>S72-15E</u>	_____	_____	_____
Distance	<u>61Ls</u>	_____	_____	_____

Bearing Trees, Reference Objects

_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
CERTIFICATE - MILO STEFAN - 1974 - FILED IN 1977
Doc. # 246218
Found GLO monument in good condition
13" W. Oak N19E 36.00'
17" W. Pine N50W 46.60'
20" W. Pine S55W 55.50'
18" W. Pine N1E 64.00'

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____