


Index No. A1

CASS COUNTY LAND CORNER RECORD

T. 144 R. 31 M. 5TH Coordinates: X _____ Y _____
NW 6 Corner common to sections 6



EXISTING SURVEYS

Original Government Survey

Year surveyed 1871
Original monument Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing	Trees		
<u>W. Pine</u>	<u>79m</u>	<u>W. Pine</u>	<u>W. Pine</u>	
<u>30"</u>	<u>10"</u>	<u>30"</u>	<u>30"</u>	
<u>N80E</u>	<u>N85W</u>	<u>S4E</u>	<u>S 5W</u>	
<u>100 LKS</u>	<u>58 LKS</u>	<u>44 2 LKS</u>	<u>471 LKS</u>	

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1913 By John Curo
Location filed County Survey Record Book "B" P.36-39
Monument SET 2x48" GALV. I.P.

Evidence of Subsequent Corner Restoration

Year of search 3/2001 By CCSO
Found Alum. cap tel spar, up. 1.0',
43± NE of & CR#69 near PI, Survey
Marker Sign South 3.0'

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Bearing Trees, Reference Objects

<u>W. Oak</u>	<u>W. Oak</u>	_____	_____
<u>15"</u>	<u>15"</u>	_____	_____
<u>N62°E</u>	<u>East</u>	_____	_____
<u>192.56'</u>	<u>144.94'</u>	_____	_____

*distance to double head nail & disk

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____